



Idinio Smart WiFi LED dimmer 200W



With this smart wifi dimmer you can control the lights with both the panel self or with the Idinio app on your phone or Google Home / Alexa. A unique solution! Suitable for LED and incandescent bulbs. Only suitable for a 3-wire system. A 3-wire system contains both a brown, black and blue wire in the flush-mounted box of the switch (even if there is / does not need to be a socket there). In contrast to a 2-wire system, an 'extra' blue (zero) wire is standardly extended from the central box in the ceiling (near the lamp) to the flush-mounted boxes of the switches.

Article number 140190

EAN 8719323789128

Brand



Smart switching and dimming

Compatible with	3-wire systems
Neutral required	Yes
Fits to European frames and switch paddles	Yes
Fits to European flush cans	Yes
Min. depth of built-in installation box	34.00 mm
Memory function (colour / dim)	Yes
Max. load INC/HAL	300 W
Max. load LED	200 VA

Smart home

Smart home category	Smart dimming and switching
Compatible with operating system	Android, iOS
Smart home platform	Idinio app, Google Assistant, Amazon Alexa
Smart home protocol	Tuya
Method of operation	App, Manually, Speech
Area of application	Indoor
On/off switch	Yes
Reset button	Yes

Performance parameters

IP rating	IP20
Operating temperature	-10 40 °C

Mechanical parameters

Dimension of article length	71 mm
Dimension of article height	34 mm
Dimension of article width	71 mm
Net weight of article	0.06 kg
Color housing	Yellow

Logistic data

Single packing dimension length	7.50 cm
Single packing dimension width	7.50 cm
Single packing dimension height	5.00 cm
Single packing gross weight	0.09 kg
Master carton dimension length	33.00 cm
Master carton dimension width	55.00 cm

Time schedule can be set	Yes	Master carton dimension	40.00 cm
Network connection type	Wireless	height	
Wifi protocol	802.11b, 802.11g, 802.11n	Quantity in master carton	200 pcs.
Wifi frequency band	2.4GHz	Master carton gross	17.80 kg
Network security protocols	WPA, WPA2	weight	
Antenna gain	2.50 dBi	CBM of master carton	0.07 m ³

Electrical parameters

Input voltage	220 240 V
Input frequency	50 Hz
Input current	1.30 A
Power factor	0.95
Dimming methods	Trailing-edge