



PSK01 Z-Wave Smart Keyboard

- Multi-functions smart switch for home automation or security application
- Leading Code Function
- Support Security 2 Function
- Elegant glass touch panel white/black color optional
- Programmed button to control Z-Wave devices
- Low Power Consumption
- Green and Red LED Indicator
- Interactive with other Devices
- Linux-based, providing the SoC with a comprehensive protocol stack for customized integration



Rated Voltage	5V/1A (Micro USB charging for battery)
RF distance	Min. 40M indoor, 100M outdoor line of sight,
RF Frequency	908.4MHz,916MHz (U.S. A./Mexico) 868.4MH, 869.85MHz (EU) 922.5MHz, 923.9MHz, 926.3MHz (JP) Transceiver
Chip	Z-wave 500 Series Module
Battery Lifetime	6 months
Alarm Audibility	85 dB/3M
Dimension	122(L) x 92(W) x 15.65(H) mm
Weight	210g
IP classification	indoor use
Operation Temperature	0 ~ 40°C
Operation Humidity	85%RH max



PHILIO TECHNOLOGY CORPORATION

8F., No. 653-2, Zhongzheng Rd., Xinzhuang Dist., New Taipei City 24257, Taiwan
 sales@philio-tech.com Tel:+886-2-2908-8952 Fax:+886-2-29088652