

Light/Shutter Control II

Product Information Sheet

Multifunctional use: Intelligent control of lighting or shading (by shutters, blinds or awnings) - easily selectable during initial installation.

- **Precise shutter control:** Conveniently moves shutters, blinds or awnings exactly to the desired position of height as well as tilt.
- **Flexible 2-in-1 light control:** Can control two lamps individually as in a series circuit.
- **Invisible smartness:** Can be flexibly installed in flush-mounted or surface-mounted boxes.
- **Overview of power consumption:** Measures the energy consumption of the connected lamps and thus helps to save energy.
- **Flexible operation:** Can be controlled directly at the switch, by voice, via individual scenarios, automations, timers or via app - at home or on the go.
- **Extension of the radio signal:** Extends the range of the radio signal for certain Bosch Smart Home devices to remote, previously unreachable rooms.
- **Endless possibilities:** Integration with Apple HomeKit, Amazon and Google Home enables combination with compatible devices from additional manufacturers.

Specification	Technical Data
Power supply	230V / 50Hz
Applications/use in	Indoor (IP20) / Temperature range -20 to +50C
Shutter max. load	<= 400W
Light max load	<= 200 W LED or inductive load per channel / <= 500 W resistive load per channel
Package Dimension (B x T x H)	B 92 / T 52,75 / H 91 mm
Positioning	In wall bracket or installation box
Radio Standard	Zigbee 2.4 GHz, Signal extension (Zigbee repeater)



* When installing in a wall box together with a switch, the box must have sufficient depth (approx. 50 mm).

Description	Order number	EAN-Code		
Light/Shutter Control II	8-750-002-078	4062321596019		

1

Intern | HOME/PRM-UX | 19.01.2022

© Robert Bosch GmbH 2022. Alle Rechte vorbehalten, auch bzgl. jeder Verfügung, Verwertung, Reproduktion, Bearbeitung, Weitergabe sowie für den Fall von Schutzrechtsanmeldungen.

 **BOSCH**