## **SHADA**

## WiFI Ceiling Light with Google Nest Mini and Amazon Echo Dot Bracket



## In stock

- Bracket for smart home speaker
- RGB Backlight
- Easy installation and assembly

The unique and space saving Wi-Fi Led Ceiling Light with Docking combines the most popular smart speakers with Tuya powered smart lighting. Ideal for living rooms, bedrooms, kitchens, or hallways.

The lamp has a diameter of 50 centimeters and includes several black and white brackets, in which a Google Nest Mini 2nd Gen or an Echo Dot 3rd/4th Gen can be installed. In addition, the lamp includes an integrated smart speaker power supply. After installation, the luminaire can be controlled via Google Assistant or Amazon Alexa when the smart speaker app is connected to the Idinio app.

The right atmosphere can be created by easily adjusting the different colors of the lamp. The front light can be set from extra warm to cold white light and is dimmable. The backlight includes different RGB colors and can also be dimmed. Furthermore, the luminaire offers additional functions, namely:

- A music function where the light reacts to the music that is being played.
- Creating your own scenes or using other scenes for specific applications such as reading or watching TV
- Setting a timer or schedule when the ceiling light is supposed to turn on or off.
- Wake up with the lamp due to the integrated bio rhythm function that simulates the rising sun.

The ceiling light is easy to install and assemble and no smart hub is necessary, just your Wi-Fi router.

Combine this lamp with the other smart home products for the ultimate smart home experience.

Download the Idinio app in the Google Play Store or the Apple App store.

Article number 0140148



Performance

General





dericiai		1 CHOITHAILCE	
Warranty	2-Year	IP Rating	IP20
Compliance certificates	CE	Impact strength	None
Manual language	Dutch, English, French,	Operating Temperature	-10 — 45 °C
	German, Spanish	Energy class (EU	A++
PLC Status	Active	874/2012)	
Package content	Quickstart guide,	Energy class (EU	F
	Screws and plugs,	2019/2015)	
	Mounting bracket	Eprel ID	734083
Lighting		Mechanical	
Total lumens	1700 lm	Color housing	White
Useful lumens	350 lm	Diffuser material	Polymethyl
Lamp efficacy	515		methacrylate (PMMA)
Light sharing	Symmetric	Housing material	Polypropylene (PP)
Color temperature	2000 K, 4000 K	Diffuser finishing	Opal
Color temperature range	2000 — 4000 K	Article height	72 mm
Color description	Neutral white, Warm	Article outer diameter	500.00 mm
	white	Article net weight	1500 g
Color rendering index	80		
Color consistency	SDCM6	Logistic Data	
(McAdam Ellipse)		Packaging length	55.5 cm
Beam angle	150 °	Packaging width	9.0 cm
Photobiological safety	RG1	Packaging height	55.0 cm
according to EN 62471		Packaging gross weight	2350.0 g
Consumble		EAN Product	8720246202472
Smart Home		Packaging paper material	882.0 g
Compatible with	iOS, Android	weight	
operating system		Packaging plastic material	118.00 g
Method of operation	App, Speech	weight	
Network connection type		Master carton length	56 cm
Network security	WPA, WPA2	Master carton width	29 cm
protocols		Master carton height	56 cm
Smart home category	Smart lighting	CBM master carton	$0.09 \text{ m}^3$
Smart home platform	Idinio app, Google	Master carton quantity	3
	Assistant, Amazon	Master carton gross	7.60 kg
	Alexa	weight	
Smart home protocol	Tuya	Master carton paper	3146.00 g
Wifi frequency band (ghz)	2.4GHz	material weight	25.4.00
Wifi protocol	802.11b, 802.11g,	Master carton plastic	354.00 g
Time a Cab a ded a Constitution	802.11n	material weight	42
Time Schedule Can Be Set	Yes	EU pallet quantity	42

Antenna gain

1.5 dBi

Country of Origin

HS Code

9405403990

Electrical

Power consumption

3.3 W

Input voltage

220 — 240 V

Voltage type AC
Input frequency 50/60 Hz
Power factor 0.87
Input current 116 mA
Safety class II

Control gear type Driver on board

Maximum qty per 16A 44

type B circuit breaker

Maximum qty per 16A 70

type C circuit breaker

LED chip type SMD 2835
LED chip brand Sanan
LED chip quantity 56
Input power 24.00 W