


HEIMAN®



HEIMAN

Smart Siren

SKU: HS2WD-Z



Quickstart

This is a **secure Siren** for **CEPT (Europe)**. Please make sure the internal battery is fully charged. To add this device to your network execute the following action:

Click [Add] icon in Z-Wave Controller.-Press the Net_Button 3 times within 1.5s, Green LED is Blinking 3 times within 1 .5second.-If add Process is successful, Green LED will turn off.

Attention: This manual is automatically generated from [Z-Wave Alliance](#) Product data and may be incomplete. Please refer to the [Manufacturers Manual](#) for more information.

Important safety information

Please read this manual carefully. Failure to follow the recommendations in this manual may be dangerous or may violate the law. The manufacturer, importer, distributor and seller shall not be liable for any loss or damage resulting from failure to comply with the instructions in this manual or any other material. Use this equipment only for its intended purpose. Follow the disposal instructions. Do not dispose of electronic equipment or batteries in a fire or near open heat sources.

What is Z-Wave?

Z-Wave is the international wireless protocol for communication in the Smart Home. This device is suited for use in the region mentioned in the Quickstart section.

Z-Wave ensures a reliable communication by reconfirming every message (**two-way communication**) and every mains powered node can act as a repeater for other nodes (**meshed network**) in case the receiver is not in direct wireless range of the transmitter.

This device and every other certified Z-Wave device can be **used together with any other certified Z-Wave device regardless of brand and origin** as long as both are suited for the same frequency range.

If a device supports **secure communication** it will communicate with other devices secure as long as this device provides the same or a higher level of security. Otherwise it will automatically turn into a lower level of security to maintain backward compatibility.

For more information about Z-Wave technology, devices, white papers etc. please refer to www.z-wave.info.



Product Description

The Smart Siren is designed to issue alarms to scare off intruder. This Smart Siren adopts z-wave technology, if a z-wave network is built in the user's home, office, warehouse or other places, when an alarm in the z-wave network is triggered, this Smart Siren will issue high decibel sound and light alarms, and alarm information will also be sent to the user's phone App.

Prepare for Installation / Reset

Please read the user manual before installing the product.

In order to include (add) a Z-Wave device to a network it **must be in factory default state**. Please make sure to reset the device into factory default. You can do this by performing an Exclusion operation as described below in the manual. Every Z-Wave controller is able to perform this operation however it is recommended to use the primary controller of the previous network to make sure the very device is excluded properly from this network.

Reset to factory default

This device also allows to be reset without any involvement of a Z-Wave controller. This procedure should only be used when the primary controller is inoperable.

-Long press Net_Button at least 10 seconds in the product.

Inclusion/Exclusion

On factory default the device does not belong to any Z-Wave network. The device needs to be **added to an existing wireless network** to communicate with the devices of this network. This process is called **Inclusion**.

Devices can also be removed from a network. This process is called **Exclusion**. Both processes are initiated by the primary controller of the Z-Wave network. This controller is turned into exclusion respective inclusion mode. Inclusion and Exclusion is then performed doing a special manual action right on the device.

Inclusion

Click [Add] icon in Z-Wave Controller.-Press the Net_Button 3 times within 1.5s, Green LED is Blinking 3 times within 1 .5second.-If add Process is successful, Green LED will turn off.

Exclusion

-Click [Remove] icon in Z-Wave Controller. -Press the Net_Button 3 times within 1.5second. -If remove Process is successful, Green LED is Blinking 6 times, then turn off.

Quick trouble shooting

Here are a few hints for network installation if things dont work as expected.

1. Make sure a device is in factory reset state before including. In doubt exclude before include.
2. If inclusion still fails, check if both devices use the same frequency.
3. Remove all dead devices from associations. Otherwise you will see severe delays.
4. Never use sleeping battery devices without a central controller.
5. Dont poll FLIRS devices.
6. Make sure to have enough mains powered device to benefit from the meshing

Association - one device controls an other device

Z-Wave devices control other Z-Wave devices. The relationship between one device controlling another device is called association. In order to control a different device, the controlling device needs to maintain a list of devices that will receive controlling commands. These lists are called association groups and they are always related to certain events (e.g. button pressed, sensor triggers, ...). In case the event happens all devices stored in the respective association group will receive the same wireless command wireless command, typically a 'Basic Set' Command.

Association Groups:

Group Number	Maximum Nodes	Description
1	5	Association group 1: Lifeline association groupInclude command classes: Switch Binary report ,Battery and Device Reset Locally notification.

Technical Data

Hardware Platform	ZM5202
Device Type	Siren
Network Operation	Always On Slave
Firmware Version	HW: 255 FW: 1.02
Z-Wave Version	6.71.03
Certification ID	ZC10-18066158
Z-Wave Product Id	0x0260.0x8009.0x1000
Firmware Updatable	Updatable by Consumer by RF
Color	White
Security V2	S2_UNAUTHENTICATED
Frequency	XXfrequency
Maximum transmission power	XXantenna

Supported Command Classes

- Association Grp Info
- Association V2
- Basic V2
- Battery
- Device Reset Locally
- Firmware Update Md V4
- Manufacturer Specific V2

- Multi Channel Association V3
- Powerlevel
- Security
- Security 2
- Supervision
- Switch Binary
- Transport Service V2
- Version V3
- Zwaveplus Info V2

Explanation of Z-Wave specific terms

- **Controller** — is a Z-Wave device with capabilities to manage the network. Controllers are typically Gateways, Remote Controls or battery operated wall controllers.
- **Slave** — is a Z-Wave device without capabilities to manage the network. Slaves can be sensors, actuators and even remote controls.
- **Primary Controller** — is the central organizer of the network. It must be a controller. There can be only one primary controller in a Z-Wave network.
- **Inclusion** — is the process of adding new Z-Wave devices into a network.
- **Exclusion** — is the process of removing Z-Wave devices from the network.
- **Association** — is a control relationship between a controlling device and a controlled device.
- **Wakeup Notification** — is a special wireless message issued by a Z-Wave device to announce that it is able to communicate.
- **Node Information Frame** — is a special wireless message issued by a Z-Wave device to announce its capabilities and functions.

(c) 2022 Z-Wave Europe GmbH, Antonstr. 3, 09337 Hohenstein-Ernstthal, Germany, All rights reserved, www.zwave.eu. The template is maintained by [Z-Wave Europe GmbH](#). The product content is maintained by Z-Wave Alliance , Certification Team, christian@z-wavealliance.org. Last update of the product data: 10.03.2022