

RLC-822A-IP-Camera-Specifications		
	Model	RLC-822A
Video & Audio	Image Sensor	1/2.8" CMOS Sensor
	Video Resolution	Default: 3840X2160 (8.0 megapixels) at 25 frames/sec
	Lens	f=2.8-8mm, F=1.6, with IR cut
	Optical Zoom	3X
	Video Format	H.265
	Field of View	Horizontal: 94°-50°
		Vertical: 53°-30°
	Day & Night	Auto-switching with IR-cut filter
	Night Vision	30 meters (100 ft) (LED: 18pcs/14mil/850nm)
Audio	Audio recording	
Power	PoE	IEEE 802.3af, 48V active
	DC Power	DC 12.0V=1A, <12W
	Power	DC power port
Interface	System	Reset button
	Ethernet	One 10M/100Mbps; RJ45
	Storage	Micro SD card slot (Max. 256GB)
	Audio	Built-in microphone
	Frame Rate	Mainstream: 2fps - 25fps (default: 25fps) Substream: 4fps - 15fps (default: 10fps)
Software Features	Code Rate	Mainstream: 1024Kbps - 8192Kbps (default: 6144Kbps)
		Substream: 64Kbps - 512Kbps (default: 256Kbps)
	Browsers Supported	Edge, Chrome, Firefox, Safari
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
	Smart Alarm	Motion detection; person detection; vehicle detection; pet detection (beta)
	Record Mode	Motion-triggered recording (default); scheduled recording; 24/7 recording
	Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
	Maximal User Access	20 users (1 admin account & 19 user accounts); supports up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Working Environment	Work with	Google Assistant
	Temperature	Operating temperature: -10°C~+55°C (14°F~131°F)
	Humidity	Operating humidity: 10% ~ 90%
	Waterproof	IP66
Size & Weight	Dimension	Φ105*95mm
	Weight	467.5g
	Warranty	Limited Warranty
		2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/